

Gliederkette-GKD

# AUSWAHLTABELLE

MODULARE ROHRDICHTUNG – GLIEDERKETTE GKD – AUSWAHLTABELLE					
Ø <sub>i</sub> -Maueröffnung innen (mm)	Ø <sub>a</sub> -Medienrohr außen (mm)		Anzahl Segmente	Type GKD	min. Einbautiefe
	von	bis			
65	25	33	6	275	75
	34	37	5	200	75
	38	39	6	200	75
70	30	33	7	275	75
	34	38	7	275	75
	39	44	6	200	75
80	40	48	8	275	75
	48	54	7	200	75
100	42	43	5	340	120
	44	49	6	340	120
	58	63	6	300	100
	64	67	10	275	75
	68	68	11	275	75
	69	74	9	200	75
125	73	78	8	315	100
	79	88	8	300	100
	89	90	13	275	75
	91	93	14	275	75
	94	99	12	200	75
150	61	76	5	410	140
	66	74	6	360	120
	77	86	7	360	120
	82	99	9	340	120
	98	103	10	315	100
	104	113	10	300	100
	118	120	14	200	75
	121	124	15	200	75
200	103	124	7	410	140
	115	117	7	475	150
	116	132	9	360	120
	125	126	8	410	140
	133	136	10	360	120
	136	149	13	340	120
	148	152	14	315	100
	154	160	13	300	100
	161	163	14	300	100
	168	174	20	200	75

Gliederkette-GKD

# AUSWAHLTABELLE

MODULARE ROHRDICHTUNG – GLIEDERKETTE GKD – AUSWAHLTABELLE					
Ø <sub>i</sub> -Maueröffnung innen (mm)	Ø <sub>a</sub> -Medienrohr außen (mm)		Anzahl Segmente	Type GKD	min. Einbautiefe
	von	bis			
250	153	166	9	410	140
	153	166	9	475	150
	162	177	7	400	150
	166	182	12	360	120
	167	167	10	475	150
	182	188	16	340	120
	190	202	9	325	110
	192	199	17	340	120
	198	199	18	315	100
	203	203	19	315	100
	204	213	17	300	100
	218	224	25	200	75
300	157	167	7	500	165
	168	176	8	500	165
	178	184	8	525	165
	185	195	10	575	165
	203	203	11	475	150
	203	204	11	410	140
	209	217	12	475	150
	209	226	12	410	140
	215	227	9	400	150
	216	235	15	360	120
	228	242	9	425	125
	232	245	20	340	120
	240	252	11	325	110
	249	249	21	340	120
	250	253	23	315	100
268	274	31	200	75	

Gliederkette-GKD

# AUSWAHLTABELLE

MODULARE ROHRDICHTUNG – GLIEDERKETTE GKD – AUSWAHLTABELLE					
Ø <sub>i</sub> -Maueröffnung innen (mm)	Ø <sub>a</sub> -Medienrohr außen (mm)		Anzahl Segmente	Type GKD	min. Einbautiefe
	von	bis			
350	207	222	9	500	165
	223	234	9	525	165
	237	250	12	575	165
	246	252	9	440	150
	253	267	14	475	150
	253	276	14	410	140
	253	260	10	440	150
	264	277	10	400	150
	266	287	18	360	120
	278	292	11	425	125
	282	289	24	340	120
	290	302	13	325	110
	293	299	25	340	120
	298	303	27	315	100
	304	313	25	300	100
318	323	36	200	75	
400	262	276	11	500	165
	273	284	11	525	165
	288	300	14	575	165
	296	310	11	440	150
	303	317	16	475	150
	303	323	16	410	140
	314	327	12	400	150
	316	336	21	360	120
	328	341	12	425	125
	340	352	15	325	110
	342	342	13	425	125

Gliederkette-GKD

# AUSWAHLTABELLE

MODULARE ROHRDICHTUNG – GLIEDERKETTE GKD – AUSWAHLTABELLE					
Ø <sub>i</sub> -Maueröffnung innen (mm)	Ø <sub>a</sub> -Medienrohr außen (mm)		Anzahl Segmente	Type GKD	min. Einbautiefe
	von	bis			
450	307	326	12	500	165
	323	332	12	525	165
	339	350	16	575	165
	350	360	13	440	150
	353	360	18	475	150
	364	377	14	400	150
	365	367	19	475	150
	366	386	24	360	120
	378	392	14	425	125
	390	402	17	325	110
500	332	346	13	650	165
	357	376	14	500	165
	374	384	14	525	165
	384	384	17	575	165
	390	400	18	575	165
	396	410	14	440	150
	403	417	21	475	150
	414	427	15	400	150
	428	442	16	425	125
	440	452	19	325	110
	448	453	39	315	100
	454	463	36	300	100
550	350	370	9	615	205
	385	396	15	650	165
	407	417	15	650	165
	424	426	16	500	150
	427	434	16	500	150
	434	435	19	575	165
	441	450	20	575	165
	446	460	16	440	150
	453	467	23	475	150
	464	477	17	400	150
	478	488	17	425	125
	490	502	21	325	110

# Gliederkette-GKD

## AUSWAHLTABELLE

MODULARE ROHRDICHTUNG – GLIEDERKETTE GKD – AUSWAHLTABELLE					
Ø <sub>i</sub> -Maueröffnung innen (mm)	Ø <sub>a</sub> -Medienrohr außen (mm)		Anzahl Segmente	Type GKD	min. Einbautiefe
	von	bis			
600	400	420	10	615	205
	432	446	16	650	165
	457	476	17	500	165
	473	484	17	525	165
	484	486	21	575	165
	487	500	22	575	165
	496	510	17	440	150
	503	516	25	475	150
	514	527	19	400	150
	517	517	26	475	150
	528	542	19	425	125
	540	552	23	325	110
	650	450	470	11	615
482		496	18	650	165
507		526	19	500	165
523		534	19	525	165
534		537	23	575	165
543		550	24	575	165
546		560	19	440	150
553		554	27	475	150
559		567	28	475	150
564		576	20	400	150
578		592	21	425	125
590	602	25	325	110	

Unsere Kundenberater stehen Ihnen bei sämtlichen Fragen rund um unsere Produkte und Dienstleistungen mit Rat und Tat zur Seite.

### Hauff-Technik GmbH & Co. KG

Robert-Bosch-Straße 9  
89568 Hermaringen, GERMANY

Tel. +49 7322 1333-0  
Fax +49 7322 1333-999

office@hauff-technik.de